









Quilt designed by Heidi Pridemore for Blank Quilting

Fabric Requirements:

	Yardage	Bright Version	Neutral Version
Fabric A:	1/4 yd	6849 Bright	6849 Neutral
Fabric B:	1/4 yd	6850 Bright	6850 Neutral
Fabric C:	1-1/8 yds	6848 Bright	6848 Neutral
Fabric D:	3/8 yd	6383 Royal	6843 Heather
Fabric E:	1/4 yd	6383 Turquoise	4368 Charcoal
Fabric F:	1/6 yd	6383 Lime	3504 Cocoa
Fabric G:	1/6 yd	6383 Grape	6343 Black
Fabric H:	1 yd	6383 Orange	4368 Cocoa
Fabric I:	1/4 yd	6383 Pink	3504 Wine
Fabric J:	1/6 yd	6383 Yellow	4368 Latte
Fabric K:	1-1/2 yds	3599 White	4368 Ivory
Backing:	3-1/4 yds	6849 White	6849 Neutral

Cutting Instructions:

- **Fabric A:** Cut one 6-1/2" x width of fabric (WOF) strip. Sub-cut the strip into four 6-1/2" squares.
- **Fabric B:** Cut two 3-1/2" x WOF strips.
- Fabric C: Cut one 6-1/2" x WOF strip. Sub-cut the strip into four 6-1/2" squares.

 Cut three 4-1/2" x WOF strips. Sew the strips together and cut two 4-1/2" x 51-1/2" strips.

 Cut three 4-1/2" x WOF strips. Sew the strips together and cut two 4-1/2" x 47-1/2" strips.
- Fabric D: Cut two 3-1/2" x WOF strips.

 See instructions to cut three scissor halves with the small eye.

 See instructions to cut three large inner buttons.
- Fabric E: See instructions to cut three scissor halves with the large eye.

 See instructions to five ripper tops.

 See instructions to twenty pin bottoms.
- **Fabric F:** See instructions to cut twelve spool ends.
- **Fabric G:** See instructions to cut four pin cushion bottoms. See instructions to cut three scissor rivets. See instructions to cut three large outer buttons.

- Fabric H: Cut three 2" x WOF strips.

 Sew the strips together and cut two 2" x 48-1/2" strips.

 Cut two 2" x 39-1/2" strips.

 Cut six 2-1/2" x WOF strips for the binding.


 See instructions to cut six small outer buttons.

 See instructions to cut twelve pin heads.

 See instructions to cut two spools.
- Fabric I: See instructions to cut four pin cushion tops.
 See instructions to cut six small inner buttons.
 See instructions to cut five ripper handles.
 See instructions to cut two spools.
- **Fabric J:** See instructions to cut eight pin heads. See instructions to cut two spools.
- **Fabric K:** Cut three 8-1/2" x 48-1/2" strips from the length of fabric (LOF).
- **Backing:** Cut two 55" x WOF strips. Piece the strips together and trim the 55" x 67" back.

Column Assembly Instructions:

- 1. Following the manufacturer's instructions, trace the listed number of each template onto the paper side of the fusible web. Roughly cut out each template about 1/8" outside the drawn lines.
- 2. Press each template onto the wrong side of the fabrics as listed on the templates. Cut out each template on the drawn lines.
- 3. Refer to the quilt photo to arrange and press the sewing notions onto the three 8-1/2" x 48-1/2" Fabric K strips.
- **4.** Finish the raw edges of each shape with a decorative stitch such as a buttonhole or satin stitch to complete the three applique columns as shown.
- 5. Sew one 3-1/2" x WOF Fabric B strip, lengthwise, to one 3-1/2" x WOF Fabric D strip to make one B/D strip (Fig. 1). Repeat to make a second B/D strip. Sub-cut the B/D strips into sixteen 3-1/2" x 6-1/2" strips (Fig. 2).
- 6. Sew two of the B/D 3-1/2" x 6-1/2" strips together to make one B/D fourpatch block (Fig. 3). Repeat to make eight B/D four-patch blocks total.
- 7. Sew two 6-1/2" Fabric A squares, four B/D four-patch blocks and two 6-1/2" Fabric C squares together to make one pieced column. Repeat to make a second pieced column.



- 8. Sew the three applique columns and the two pieced columns together, alternating them, to make the quilt top.
- 9. Sew one 2" x 48-1/2" Fabric H strip to each side of the quilt top. Sew one 2" x 39-1/2" Fabric H strip to the top and bottom of the quilt top.
- 10. Sew one 4-1/2" x 51-1/2" Fabric C strip to each side of the quilt top. Sew one 4-1/2" x 47-1/2" Fabric C strip to the top and bottom of the quilt top.
- 11. Layer and quilt as desired.
- 12. Sew the six 2-1/2" x WOF binding strips together, end to end with 45° seams, to make the binding. Fold this long strip in half lengthwise with wrong sides together and press.
- 13. Bind as desired.

